# NSN 5930-01-238-2212

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-2212

#### **Thread Class:**

2a single mounting facility

### **Thread Length:**

0.375 inches single mounting facility

# **Overall Length:**

4.063 inches

#### **Overall Width:**

Between 1.953 inches and 1.983 inches

#### Shaft Diameter:

0.247 inches single actuator and 0.250 inches single actuator

#### Shaft Length:

0.500 inches single actuator

#### Nonturn Device Radius:

0.521 inches at 12: 00 o'clock and 0.541 inches at 12: 00 o'clock

# Individual Section Quantity:

6

#### Nonturn Device Type:

Tab at 12: 00 o'clock

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section rear

#### Throw Quantity:

23 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

# Switch Actuator Indexing Position Quantity:

23 single actuator

#### Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

### **Contact Switching Action:**

Makes before breaks 4th section rear

#### Switch Actuator Positioning Increment:

15.0 degrees single actuator

### **Precious Material And Location:**

Clips and rotor blades silver

#### **Precious Material:**

Silver

# NSN 5930-01-238-2212

Rotary Switch - Page 2 of 2

Style Designator:

Circular wafer, bushing mount

# Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

# Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A052b0

