NSN 5930-01-238-2223

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-2223

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Salt spray resistant and moisture resistant and explosion proof

Overall Length:

0.750 inches

Overall Height:

2.010 inches

Overall Width:

0.750 inches

Body Length:

0.688 inches

Body Width:

0.688 inches

Case Material:

Metal

Actuator Length:

J

0.620 inches

Actuator Style:

Rectangular

Actuator Height:

0.125 inches

Actuator Width:

0.620 inches

Actuator Color:

Black single actuator

Illuminated Actuator Color:

Red single actuator

Actuator Inscription:

Aft fire single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

Special Features:

T-1 lamp bulb size

NSN 5930-01-238-2223

Push Switch - Page 2 of 2



Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

3 turret and 6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0