

View Online at <https://aerobasegroup.com/nsn/5930-01-238-2906>

Thread Class:

2a single mounting facility

Thread Length:

0.312 inches single mounting facility

Overall Length:

Between 2.431 inches and 2.523 inches

Overall Height:

Between 0.851 inches and 0.871 inches

Overall Width:

Between 0.860 inches and 0.890 inches

First Flat Length:

0.250 inches 1st actuator 0.250 inches 2nd actuator

Flat Height:

0.219 inches 1st actuator 0.094 inches 2nd actuator

Shaft Diameter:

0.250 inches 1st actuator 0.125 inches 2nd actuator

Shaft Length:

0.375 inches 1st actuator 0.750 inches 2nd actuator

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

12 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round, hollowed, flatted 1st actuator round, flatted 2nd actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

150.0 milliamperes resistive load ac at sea level 30.0 milliamperes inductive load dc at sea level and 200.0 milliamperes resistive load dc at sea level

Precious Material And Location:

Contact and rotor blade surfaces silver and contact and rotor blade surfaces gold

Precious Material:

Silver and gold

Style Designator:

Wafer, printed board, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0