NSN 5930-01-238-4079

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-4079

| Body Style: | | | |
|--|--|--|--|
| Panel mount | | | |
| Hazardous Locations/environmental Protection: | | | |
| Driptight and dustproof | | | |
| Overall Length: | | | |
| 0.960 inches | | | |
| Overall Height: | | | |
| 2.355 inches | | | |
| Overall Width: | | | |
| 0.960 inches | | | |
| Body Length: | | | |
| 0.688 inches | | | |
| Body Width: | | | |
| 0.960 inches | | | |
| Body Height: | | | |
| 2.115 inches | | | |
| Case Material: | | | |
| Metal | | | |
| Actuator Length: | | | |
| 0.620 inches | | | |
| Actuator Style: | | | |
| Rectangular | | | |
| Actuator Height: | | | |
| 0.125 inches | | | |
| Actuator Width: | | | |
| 0.620 inches | | | |
| Actuator Color: | | | |
| Black single actuator | | | |
| Illuminated Actuator Color: | | | |
| White single actuator | | | |
| Actuator Inscription: | | | |
| Stbd bcn single actuator | | | |
| Maximum Voltage Rating In Volts: | | | |
| 115.0 ac and 28.0 dc | | | |
| Inclosure Type: | | | |
| Fully enclosed | | | |
| Mounting Method: | | | |
| Panel | | | |
| Features Provided: | | | |
| Actuator seal | | | |
| Nonpile-up Contact Arrangement: | | | |
| 4 pole, double throw, both positions maintained single switch unit | | | |

NSN 5930-01-238-4079

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

| Spe | ecial | Feat | ures: |
|-----|-------|--------|-------|
| T-1 | lamı | o bulb | size |

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0