## NSN 5930-01-238-4088

Push Switch - Page 1 of 2

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5930-01-238-4088

Panel mount
Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
0.960 inches
Overall Height:
2.355 inches
Overall Width:
0.960 inches
Body Length:
0.688 inches
Body Width:
0.960 inches
Body Height:
2.115 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.125 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Blue single actuator and white single actuator
Actuator Inscription:
2jg1 sel single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
4 pole, double throw, both positions maintained single switch unit

## NSN 5930-01-238-4088

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

## **Special Features:**

T-1 lamp bulb size, split lens

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

12 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0