# NSN 5930-01-238-4092

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-4092

# **Body Style:**

Panel mount

# Hazardous Locations/environmental Protection:

Driptight and dustproof

## **Overall Length:**

0.960 inches

## **Overall Height:**

2.355 inches

# **Overall Width:**

0.960 inches

#### **Body Length:**

0.688 inches

## **Body Width:**

0.960 inches

# Body Height:

2.115 inches

#### \_ .. ..

Case Material:

Metal

# Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

# Actuator Height:

0.125 inches

# Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator and black single actuator

### Illuminated Actuator Color:

Green single actuator and white single actuator

#### **Actuator Inscription:**

Mom on single actuator

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

## Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Actuator seal

### **Nonpile-up Contact Arrangement:**

4 pole, double throw, one position momentary single switch unit

# NSN 5930-01-238-4092

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes

inductive ac and 2.000 amperes lamp ac

# **Special Features:**

T-1 lamp bulb size, split lens

**Precious Material And Location:** 

Contacts silver

**Terminal Type And Quantity:** 

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0