NSN 5930-01-238-4099

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-4099

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Driptight and dustproof
Overall Length:
0.960 inches
Overall Height:
2.355 inches
Overall Width:
0.960 inches
Body Length:
0.688 inches
Body Width:
0.960 inches
Body Height:
2.115 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.125 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
White single actuator and white single actuator
Actuator Inscription:
Lso call in 2jg3 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

NSN 5930-01-238-4099

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 4.000 amperes inductive dc and 2.500 amperes lamp dc and 7.000 amperes resistive ac and 7.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

T-1 lamp bulb size, split lens

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0