## NSN 5930-01-238-4675

Thermostatic Switch - Page 1 of 2

**Thread Class:** 

Gas or liquid

2a single threaded stud



View Online at https://aerobasegroup.com/nsn/5930-01-238-4675

**Overall Length:** 0.325 inches **Overall Height:** 0.614 inches **Body Diameter:** 0.215 inches **Body Height:** 0.239 inches **End Application:** Communications control center an/tsq-111 **Tempurature Sensing Element Type:** Internal sensor **Operating Tempurature Rating:** Between -30.0 degrees fahrenheit and 365.0 degrees fahrenheit **Mounting Method:** Threaded stud **Features Provided:** Hermetically sealed case Thready Qty Per Inch (tpi): 40 single threaded stud **Contact Action Stimulus:** Increase **Thread Size:** 0.112 inches single threaded stud **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Tab, solder lug **Contact Load Current Rating:** 1.0 amperes resistive load first voltage **Contact Adjustability:** Actuation point not adjustable **Contact Stimulus Rating:** 255.00 actuation point degrees fahrenheit and 225.00 deactuation point degrees fahrenheit **Contact Voltage Rating In Volts:** 28.0 dc at sea level second voltage Frequency In Hertz: 60.0 first voltage Media For Which Designed:

## NSN 5930-01-238-4675

Thermostatic Switch - Page 2 of 2

**Style Designator:** 

Demilitarization:

No Fiig: A048b0



ISC STATE OF THE PROPERTY OF T
est Data Document:
1349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
nvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
hread Series Designator:
nc single threaded stud
pecification Data:
1349-mil-s-24236/19 government specification
helf Life:
/a
nit Of Measure: