# NSN 5930-01-238-4681

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-4681 **Thread Class:** 2a **Body Style: Bushing mount Hazardous Locations/environmental Protection:** Shock proof **Overall Length:** 0.572 inches **Overall Height:** 2.277 inches **Overall Width:** 0.364 inches **Bushing Length:** 0.469 inches **Body Length:** 0.572 inches **Body Width:** 0.364 inches **Actuator Style:** 

Round

**Actuator Diameter:** 

0.430 inches

**Actuator Height:** 

1.102 inches

#### **Actuator Position-action Relationship:**

Up position maintained and down position maintained

#### **Actuator Position-locking Relationship:**

Up position no locking action and down position no locking action and center position locked out

#### **Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

## **End Application:**

Dweapon systems-an/sqq-89 surface ship asw combat system; kidd class ddg; spruance class dd (963); aircraft, hawkeye e-2c; aircraft, e-6 tacamo; aircraft, hercules c-130f; ticonderoga class cg (47)

#### **Mounting Surface To Terminal End Distance:**

0.706 inches

#### **Inclosure Type:**

Fully enclosed

## **Mounting Method:**

Threaded bushing

#### **Features Provided:**

Actuator seal

#### Thready Qty Per Inch (tpi):

32

# **NSN 5930-01-238-4681** Toggle Switch - Page 2 of 2

A053a0



Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Criticality Code Justification:
Feat Feat
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 1.000 amperes inductive dc and 3.000 amperes resistive ac and 1.000 amperes inductive ac
Special Features:
Weapon system essential
Test Data Document:
31349-mil-s-8834 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Jns
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
96906-ms21436 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig: