

View Online at <https://aerobasegroup.com/nsn/5930-01-238-4682>

**Body Style:**

Hole mounted

**Overall Length:**

0.510 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Overall Height:**

0.520 inches

**Overall Width:**

0.210 inches

**Body Length:**

0.510 inches

**Body Width:**

0.210 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

0.088 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.062 inches

**Actuator Height:**

0.020 inches

**Actuator Free Position Height:**

0.340 inches

**Maximum Voltage Rating In Volts:**

28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:**

Single turret terminals

**Precious Material And Location:**

Terminal surfaces and contacts gold

**Test Data Document:**

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

3 turret

**Specification Data:**

81349-mil-s-8805/4 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0