NSN 5930-01-238-6724

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-238-6724

Thread	Class:
mcaa	01035.

2a

Body Style:

Bushing mounted

Overall Length:

2.532 inches

Overall Height:

0.625 inches

Overall Width:

0.625 inches

Body Diameter:

0.625 inches

Bushing Length:

0.750 inches

Body Length:

1.094 inches

Case Material:

Metal

Actuator Length:

0.500 inches

Actuator Style:

Rectangular

Actuator Height:

0.698 inches

Actuator Width:

0.500 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

White single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 30.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.500 inches

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

NSN 5930-01-238-6724

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

3.000 amperes resistive dc and 3.000 amperes resistive ac

Precious Material And Location:

Terminal surfaces and contacts silver

Thread Series Designator:

Un

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0