

View Online at <https://aerobasegroup.com/nsn/5930-01-239-1620>

Inside Diameter:

0.250 inches single connection

Overall Length:

4.000 inches

Overall Height:

5.000 inches

Overall Width:

4.500 inches

Body Length:

4.060 inches

Body Height:

4.250 inches

End Application:

Used on oil purifier model mapx-204-tgt-24-60 onboard 210 ft wmec coast guard vessels

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -4.0 degrees fahrenheit and 140.0 degrees fahrenheit

Mounting Method:

Bracket

Cubic Measure:

0.050 cubic inches

Thready Qty Per Inch (tpi):

14 single threaded hole

Contact Action Stimulus:

Increase

Thread Size:

5.000 inches single threaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

500.0 milliamperes resistive load fourth voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+6.00/+60.00 actuation point pounds per square inch gage and +6.00/+60.00 deactuation point pounds per square inch gage

Contact Adjustment Type:

Internal actuation point hex nut and internal deactuation point hex nut

Contact Voltage Rating In Volts:

250.0 dc at sea level third voltage

Pressure Connector Type:

Flare, threaded internal single connection

Special Features:

Item can accommodate interchangeable transducers

Media For Which Designed:

Liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0