## NSN 5930-01-239-1620

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-239-1620

Inside Diameter:
0.250 inches single connection
Overall Length:
4.000 inches
Overall Height:
5.000 inches
Overall Width:
4.500 inches
Body Length:
4.060 inches
Body Height:
4.250 inches
End Application:
Used on oil purifier model mapx-204-tgt-24-60 onboard 210 ft wmec coast guard vessels
Pressure Switch Type:
Gage
Operating Tempurature Rating:
Between -4.0 degrees fahrenheit and 140.0 degrees fahrenheit
Mounting Method:
Bracket
Cubic Measure:
0.050 cubic inches
Thready Qty Per Inch (tpi):
14 single threaded hole
Contact Action Stimulus:
Increase
Thread Size:
5.000 inches single threaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Screw
Contact Load Current Rating:
500.0 milliamperes resistive load fourth voltage
Contact Adjustability:
Actuation point adjustable and deactuation point adjustable
Contact Adjustment Range:
+6.00/+60.00 actuation point pounds per square inch gage and +6.00/+60.00 deactuation point pounds per square inch gage
Contact Adjustment Type:
Internal actuation point hex nut and internal deactuation point hex nut

**Contact Voltage Rating In Volts:** 

250.0 dc at sea level third voltage

## NSN 5930-01-239-1620

Pressure Switch - Page 2 of 2



Pressure Connector Type:
Flare, threaded internal single connection
Special Features:
Item can accomodate interchangeable transducers
Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Npt single threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A048b0