## NSN 5930-01-239-4023

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-239-4023

Hazardous Locations/environmental Protection:
Fungus resistant
Overall Length:
3.219 inches
Overall Height:
2.875 inches
Overall Width:
2.375 inches
Unthreaded Mounting Hole Diameter:
0.203 inches single mounting facility
Individual Section Quantity:
1
Longest Horizontal Distance Between Mounting Centers:
1.641 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
1.641 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
4 single section rear
Mounting Method:
Bracket single mounting facility and unthreaded hole single mounting facility
Features Provided:
Actuator knob
Contact Voltage Rating In Volts:
28.0 dc at sea level
Rotor Through Connection Quantity:
1 single section
Mounting Facility Pattern:
Four position rectangular single mounting facility
Switch Actuator Indexing Position Quantity:
4 single actuator
Terminal Type:
Tab w/screw
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
90.0 degrees single actuator
Contact Load Current Rating:

15.0 amperes resistive load ac at sea level

## NSN 5930-01-239-4023

Rotary Switch - Page 2 of 2



Desig	

Tap, circuit selector

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0