

View Online at <https://aerobasegroup.com/nsn/5930-01-239-4437>

**Inside Diameter:**

0.250 inches single connection

**Hazardous Locations/environmental Protection:**

Weathertight

**Overall Length:**

4.000 inches

**Overall Height:**

5.810 inches

**Overall Width:**

2.130 inches

**Body Height:**

3.000 inches

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Distance Between Mounting Facility Centers:**

2.750 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket and unthreaded hole

**Features Provided:**

Electrical access port

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

2500.00 pounds per square inch

**Thread Size:**

0.250 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Terminal Type:**

Screw

**Contact Load Current Rating:**

400.0 milliamperes resistive load second voltage

**Contact Adjustability:**

Actuation point adjustable and deactuation point adjustable

**Contact Adjustment Range:**

+10.00/+240.00 actuation point pounds per square inch and +10.00/+240.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point hex nut with scale and internal deactuation point hex nut with scale

**Contact Voltage Rating In Volts:**

480.0 ac at sea level first voltage

**Pressure Connector Type:**

Swivel nut, gasket seal, threaded internal single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Rectangular w/bracket

**Thread Series Designator:**

Nptf single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0