

View Online at <https://aerobasegroup.com/nsn/5930-01-239-4437>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Weathertight

Overall Length:

4.000 inches

Overall Height:

5.810 inches

Overall Width:

2.130 inches

Body Height:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.250 inches

Distance Between Mounting Facility Centers:

2.750 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Electrical access port

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

2500.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

400.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable and deactuation point adjustable

Contact Adjustment Range:

+10.00/+240.00 actuation point pounds per square inch and +10.00/+240.00 deactuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point hex nut with scale and internal deactuation point hex nut with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Swivel nut, gasket seal, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Rectangular w/bracket

Thread Series Designator:

Nptf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0