

View Online at <https://aerobasegroup.com/nsn/5930-01-239-5793>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock proof and watertight

Overall Length:

4.715 inches

Overall Height:

2.820 inches

Actuator Length:

1.500 inches

Actuator Style:

Roller arm

Actuator Height:

0.920 inches

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.320 inches

Housing Height:

1.780 inches

Housing Length:

2.840 inches

Housing Width:

1.650 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.340 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.160 inches

Maximum Voltage Rating In Volts:

440.0 ac and 230.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded hole

Nonpile-up Contact Arrangement:

2 pole, single throw, normally closed, momentary action single switch unit

Switch Release Force:

24.0 ounces

Switch Actuating Force:

32.0 ounces

Actuator Movement:

10.0 pretravel degrees and 40.0 overtravel degrees and 4.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

50.000 milliamperes resistive dc and 750.000 milliamperes resistive ac

Special Features:

Front mounted by two of the four mtg holes; alternatively by two 10-32 tapped holes 0.370 in. Deep for rear mount

Terminal Type And Quantity:

1 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0