NSN 5930-01-239-9658

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-239-9658

| Inside Diameter: |
|---|
| 0.250 inches single connection |
| Overall Length: |
| 5.188 inches |
| Overall Height: |
| 5.766 inches |
| Overall Width: |
| 2.812 inches |
| Body Height: |
| 2.750 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.281 inches |
| Longest Horizontal Distance Between Mounting Centers: |
| 2.406 inches |
| Shortest Horizontal Distance Between Mounting Centers: |
| 0.656 inches |
| Longest Vertical Distance Between Mounting Centers: |
| 3.281 inches |
| Pressure Switch Type: |
| Gage |
| Mounting Method: |
| Bracket and unthreaded hole |
| Features Provided: |
| Electrical access port |
| Thready Qty Per Inch (tpi): |
| 18 single pressure connection |
| Contact Action Stimulus: |
| Increase |
| Proof Pressure: |
| 80.00 pounds per square inch gage |
| Thread Size: |
| 0.250 inches single pressure connection |
| Mounting Facility Pattern: |
| Isosceles triangle |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, double break/double make, permanent jumper, both positions maintained |
| Terminal Type: |
| Screw |
| Contact Load Current Rating: |
| 9.6 amperes inductive load fifth voltage |
| Contact Adjustability: |

Actuation point adjustable

NSN 5930-01-239-9658

Pressure Switch - Page 2 of 2



| Contact Adjustment Range: |
|---|
| +13.61/+20.00 actuation point pounds per square inch gage |
| Contact Adjustment Type: |
| External actuation point hex nut |
| Contact Voltage Rating In Volts: |
| 550.0 dc at sea level eighth voltage |
| Pressure Connector Type: |
| Plain, threaded internal single connection |
| Frequency In Hertz: |
| 60.0 third voltage |
| Media For Which Designed: |
| Gas or liquid |
| Precious Material And Location: |
| Contacts silver |
| Precious Material: |
| Silver |
| Style Designator: |
| Rectangular |
| Thread Series Designator: |
| Npt single pressure connection |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A048b0