NSN 5930-01-240-0237

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-240-0237

Body Style:
Panel mounted
Hazardous Locations/environmental Protection:
Explosion proof and humidity resistant
Overall Length:
2.856 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Body Width:
0.750 inches
Body Height:
0.750 inches
Case Material:
Metal
Actuator Length:
0.620 inches
Actuator Style:
Rectangular
Actuator Height:
0.100 inches
Actuator Width:
0.620 inches
Actuator Color:
Black single actuator and black single actuator
Illuminated Actuator Color:
Red single actuator and red single actuator
Actuator Inscription:
Cat 3 suspend, local single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
Mounting Surface To Terminal End Distance:
2.756 inches
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Horizontal split lens

Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-240-0237

Push Switch - Page 2 of 2



Lower half acturator inscription sunlight readable

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0