

View Online at <https://aerobasegroup.com/nsn/5930-01-240-1893>

Overall Length:

7.100 inches

Overall Height:

2.910 inches

Overall Width:

2.810 inches

Unthreaded Mounting Hole Diameter:

0.221 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

2.000 inches single mounting facility

Shortest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.188 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

7 each section periphery

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Actuator knob

Contact Voltage Rating In Volts:

600.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Isosceles triangle single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Terminal Type:

Screw

Contact Switching Action:

Makes before breaks each section periphery

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Contact Load Current Rating:

6.0 amperes resistive load highest ac voltage rating at sea level

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0