

View Online at <https://aerobasegroup.com/nsn/5930-01-240-3025>

**Body Style:**

Panel mount

**Hazardous Locations/environmental Protection:**

Shock proof and watertight

**Overall Length:**

2.120 inches

**Overall Height:**

2.090 inches

**Overall Width:**

1.750 inches

**Body Length:**

2.120 inches

**Body Width:**

1.750 inches

**Body Height:**

1.780 inches

**Actuator Style:**

Round, flush

**Actuator Diameter:**

1.440 inches

**Actuator Height:**

0.310 inches

**Actuator Inscription:**

Slow start single actuator

**Maximum Voltage Rating In Volts:**

440.0 ac and 355.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Panel

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

500.000 milliamperes inductive dc and 5.000 amperes inductive ac

**Special Features:**

Actuator inscription is located on the perimeter of the actuator

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0