

View Online at <https://aerobasegroup.com/nsn/5930-01-240-3907>

**Thread Class:**

2a

**Body Style:**

Bushing mount

**Bushing Length:**

0.469 inches

**Body Length:**

1.312 inches

**Body Width:**

0.703 inches

**Actuator Style:**

Round

**Actuator Height:**

1.500 inches

**Actuator Position-action Relationship:**

Center position maintained and up position momentary and down position momentary

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Mounting Surface To Terminal End Distance:**

1.156 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, two positions momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0