

View Online at <https://aerobasegroup.com/nsn/5930-01-240-3907>

Thread Class:

2a

Body Style:

Bushing mount

Bushing Length:

0.469 inches

Body Length:

1.312 inches

Body Width:

0.703 inches

Actuator Style:

Round

Actuator Height:

1.500 inches

Actuator Position-action Relationship:

Center position maintained and up position momentary and down position momentary

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Mounting Surface To Terminal End Distance:

1.156 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, two positions momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

25.000 amperes resistive dc and 15.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0