NSN 5930-01-240-6451

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-240-6451

Hazardous Locations/environmental Protection:
Weatherproof
Overall Length:
2.000 inches
Outside Diameter:
0.125 inches single connection
Body Length:
0.953 inches

Overall Diameter:

1.690 inches

Pressure Switch Type:

Gage

Operating Tempurature Rating:

Between -4.0 degrees fahrenheit and 250.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

27 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

350.00 pounds per square inch

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

500.00 pounds per square inch

Terminal Type:

Tab w/screw

Contact Load Current Rating:

4.0 amperes resistive load fourth voltage

Contact Adjustability:

Actuation point not adjustable

Contact Stimulus Rating:

10.00 actuation point pounds per square inch gage

Contact Voltage Rating In Volts:

6.0 dc at sea level third voltage

Pressure Connector Type:

Plain, threaded external single connection

NSN 5930-01-240-6451

Pressure Switch - Page 2 of 2



Media For Which Designed:

Gas or liquid

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Cylindrical

Thread Series Designator:

Ptf-sae short single pressure connection

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A048b0