NSN 5930-01-240-6863

Sensitive Switch - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5930-01-240-6863

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Housing Height:

2.100 inches

Housing Length:

4.950 inches

Housing Width:

2.310 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.220 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.810 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

2 two circuit, double break/double make, both positions maintained single switch unit

Switch Release Force:

40.0 inch-ounces

Switch Actuating Force:

190.0 inch-ounces

Actuator Movement:

17.0 pretravel degrees and 63.0 overtravel degrees and 11.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

0.400 amperes inductive dc and 25.000 amperes resistive ac

Special Features:

Actuator not included

Terminal Type And Quantity:

4 screw

Reference Number Differentiating Characteristics:

Actuator shaft turns clockwise only

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0