

View Online at <https://aerobasegroup.com/nsn/5930-01-240-8117>

Hazardous Locations/environmental Protection:

Oiltight

Actuator Height:

Between 2.406 inches and 2.656 inches

Actuator Free Position Height:

Between 2.719 inches and 2.969 inches

Housing Height:

1.875 inches

Housing Length:

3.109 inches

Housing Width:

1.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.344 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.156 inches

Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Actuating Force:

49.6 ounces

Actuator Movement:

0.057 pretravel inches and 0.179 overtravel inches and 0.028 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

0.100 amperes resistive dc and 1.200 amperes resistive ac

Special Features:

Adjustable top push rod

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0