

View Online at <https://aerobasegroup.com/nsn/5930-01-240-8120>

Body Style:

Panel mount

Hazardous Locations/environmental Protection:

Corrosion proof and dustproof

Overall Height:

3.525 inches

Body Length:

1.250 inches

Body Width:

0.990 inches

Body Height:

3.150 inches

Actuator Length:

0.990 inches

Actuator Style:

Rectangular

Actuator Height:

0.300 inches

Actuator Width:

0.740 inches

Actuator Color:

White single actuator and white single actuator

Illuminated Actuator Color:

Green single actuator and green single actuator

Illuminated Actuator Color Sequence:

Top half of actuator green; bottom half of actuator green

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Fun fire control system, mk68

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Rfi shielding

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 2.500 amperes inductive ac

Test Data Document:

81349-mil-s-22885 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 socket, integrated wire termination

Specification Data:

81349-mil-s-22885/80 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0