# NSN 5930-01-242-5661

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-242-5661



## **Body Style:**

Panel mount

# Hazardous Locations/environmental Protection:

Shock resistant

# **Overall Length:**

1.200 inches

## **Overall Height:**

3.111 inches

## **Overall Width:**

0.960 inches

**Body Length:** 

Between 1.075 inches and 1.105 inches

#### **Body Width:**

Between 0.835 inches and 0.865 inches

#### **Body Height:**

## 2.970 inches

Case Material:

Metal

Actuator Length:

1.040 inches

**Actuator Style:** 

Rectangular

## Actuator Height:

0.140 inches

## Actuator Width:

0.800 inches

#### Actuator Color:

White single actuator

## Illuminated Actuator Color:

White single actuator

#### **Actuator Inscription:**

Lamp test single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Radar set an/spg-51c

# Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

NSN 5930-01-242-5661

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes resistive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes

inductive ac and 1.500 amperes lamp ac

# **Precious Material And Location:**

Contacts silver

# Terminal Type And Quantity:

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0