## NSN 5930-01-242-5667

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-5667

| Body Style:   |
|---|
| Panel mount   |
| Body Length:  |
| Between 1.075 inches and 1.105 inches                           |
| Body Width:   |
| Between 0.835 inches and 0.865 inches                           |
| Body Height:  |
| 3.110 inches  |
| Actuator Length:  |
| 1.040 inches  |
| Actuator Style:   |
| Rectangular   |
| Actuator Height:  |
| 0.140 inches  |
| Actuator Width:   |
| 0.800 inches  |
| Actuator Color:   |
| White single actuator   |
| Illuminated Actuator Color:                                     |
| Red single actuator   |
| Actuator Inscription:   |
| Break track single actuator                                     |
| Maximum Voltage Rating In Volts:                                |
| 30.0 dc   |
| End Application:  |
| Radar set an/spg-51c  |
| Inclosure Type:   |
| Uninclosed  |
| Mounting Method:  |
| Panel   |
| Features Provided:  |
| Rfi shielding   |
| Nonpile-up Contact Arrangement:                                 |
| 2 pole, double throw, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage:           |
| 1.000 amperes resistive dc and 0.500 amperes inductive dc       |
| Precious Material And Location:                                 |
| Contacts gold   |
| Terminal Type And Quantity:                                     |
| 5 tab, solder lug and 6 turret                                  |
| Shelf Life:   |

N/a

## NSN 5930-01-242-5667

Push Switch - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV  | еа  | SU  | ıre: |

--

Demilitarization:

No

Fiig:

A053a0