# NSN 5930-01-242-5682

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-5682

## **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Shock resistant

# **Overall Length:**

1.200 inches

## **Overall Height:**

3.111 inches

## **Overall Width:**

0.960 inches

#### Body Length:

Between 1.075 inches and 1.105 inches

## **Body Width:**

Between 0.835 inches and 0.865 inches

## **Body Height:**

## 2.970 inches

Case Material:

Metal

## Actuator Length:

1.040 inches

## Actuator Style:

Rectangular

## Actuator Height:

0.140 inches

# Actuator Width:

0.800 inches

## Actuator Color:

White single actuator and white single actuator

## Illuminated Actuator Color:

Yellow single actuator and yellow single actuator

#### **Actuator Inscription:**

Wide narrow single actuator

## Illuminated Actuator Color Sequence:

Upper half of actuator yellow lower half of actuator yellow

## Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

# **End Application:**

Radar set an/spg-51c

Inclosure Type:

Fully enclosed

### **Mounting Method:**

Panel

# NSN 5930-01-242-5682

Push Switch - Page 2 of 2



## Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes

inductive ac and 1.500 amperes lamp ac

Precious Material And Location:

Contacts silver

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0