# NSN 5930-01-242-5682

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-5682

Body Style:					
Panel mount					
Hazardous Locations/environmental Protection:					
Shock resistant					
Overall Length:					
1.200 inches					
Overall Height:					
3.111 inches					
Overall Width:					
0.960 inches					
Body Length:					
Between 1.075 inches and 1.105 inches					
Body Width:					
Between 0.835 inches and 0.865 inches					
Body Height:					
2.970 inches					
Case Material:					
Metal					
Actuator Length:					
1.040 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.140 inches					
Actuator Width:					
0.800 inches					
Actuator Color:					
White single actuator and white single actuator					
Illuminated Actuator Color:					
Yellow single actuator and yellow single actuator					
Actuator Inscription:					
Wide narrow single actuator					
Illuminated Actuator Color Sequence:					
Upper half of actuator yellow lower half of actuator yellow					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
End Application:					
Radar set an/spg-51c					
Inclosure Type:					
Fully enclosed					
Mounting Method:					

Panel

## NSN 5930-01-242-5682

Push Switch - Page 2 of 2



#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

### **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

_		B4 - 4 -		AI	
М	recious	wate	eriai	Ana	Location:

Contacts silver

#### **Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0