# NSN 5930-01-242-7060

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-7060

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Waterproof
Overall Length:
0.740 inches
Overall Height:
1.340 inches
Overall Width:
0.740 inches
Body Length:
0.740 inches
Body Width:
0.680 inches
Body Height:
1.000 inches
Case Material:
Metal
Actuator Length:
0.630 inches
Actuator Style:
Rectangular
Actuator Height:
0.190 inches
Actuator Width:
0.630 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Green single actuator
Actuator Inscription:
Init single actuator
Maximum Voltage Rating In Volts:
28.0 dc
End Application:
6625-01-215-6148 processor communication
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:

Actuator seal and rfi shielding

## NSN 5930-01-242-7060

Push Switch - Page 2 of 2



### **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

#### **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc

#### **Special Features:**

T-1 lamp bulb size designator

**Precious Material And Location:** 

Contacts silver

#### **Terminal Type And Quantity:**

6 tab, solder lug and 5 turret

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A053a0