## NSN 5930-01-242-7064

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-7064

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Shock resistant
Overall Length:
1.200 inches
Overall Height:
3.111 inches
Overall Width:
0.960 inches
Body Length:
Between 1.075 inches and 1.105 inches
Body Width:
Between 0.835 inches and 0.865 inches
Body Height:
2.970 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
White single actuator and white single actuator
Illuminated Actuator Color:
Green single actuator and yellow single actuator
Actuator Inscription:
Ucwim local controlucwim remote control single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator yellow lower half of actuator green
Maximum Voltage Rating In Volts:
30.0 dc
End Application:
Radar set an/spg-51c
Inclosure Type:
Fully enclosed
Mounting Method:
Panel

## NSN 5930-01-242-7064

Push Switch - Page 2 of 2



## **Nonpile-up Contact Arrangement:**

2 pole, double throw, one position momentary single switch unit

## **Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

**Special Features:** 

Split lens

**Precious Material And Location:** 

Contacts gold

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A053a0