## NSN 5930-01-242-7068

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-7068

Body Style:
Panel mount
Body Length:
Between 1.075 inches and 1.105 inches
Body Width:
Between 0.835 inches and 0.865 inches
Body Height:
3.625 inches
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
White single actuator and green single actuator
Actuator Inscription:
Radiate command, radiate complete single actuator
Illuminated Actuator Color Sequence:
Upper half of actuator white, lower half of actuator green
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Radar set an/spg-51c
Inclosure Type:
Uninclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes
inductive ac and 1.500 amperes lamp ac
Special Features:
Control capsule, panel seal
Precious Material And Location:
Contacts silver

**Terminal Type And Quantity:** 5 tab, solder lug and 12 turret

## NSN 5930-01-242-7068

Push Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0