## NSN 5930-01-242-7069

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-7069

Pody Style:
Body Style: Panel mount
Hazardous Locations/environmental Protection: Shock resistant
Overall Length: 1.200 inches
Overall Height: 3.111 inches
Overall Width:
0.960 inches
Body Length:
Between 1.075 inches and 1.105 inches
Body Width:
Between 0.835 inches and 0.865 inches
Body Height:
2.970 inches
Case Material:
Metal
Actuator Length:
1.040 inches
Actuator Style:
Rectangular
Actuator Height:
0.140 inches
Actuator Width:
0.800 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Red single actuator
Actuator Inscription:
Fault reset single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Radar set an/spg-51c
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

## NSN 5930-01-242-7069

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 2.400 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Precious	Material	And	Location:
----------	----------	-----	-----------

Contacts silver

**Terminal Type And Quantity:** 

6 turret and 5 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0