NSN 5930-01-242-7080

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-242-7080

Body Style: Panel mount Body Length: Between 1.075 inches and 1.105 inches Body Width: Between 0.835 inches and 0.865 inches Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit Contact Load Current Rating At Maximum Rated Voltage:						
Body Length: Between 1.075 inches and 1.105 inches Body Width: Between 0.835 inches and 0.865 inches Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Between 1.075 inches and 1.105 inches Body Width: Between 0.835 inches and 0.865 inches Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Body Width: Between 0.835 inches and 0.865 inches Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Between 0.835 inches and 0.865 inches Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Body Height: 3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
3.110 inches Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Length: 1.040 inches Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Style: Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Rectangular Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Height: 0.140 inches Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Width: 0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
0.800 inches Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Color: White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
White single actuator Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Illuminated Actuator Color: Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Yellow single actuator Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Actuator Inscription: Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Normal, test single actuator Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Maximum Voltage Rating In Volts: 30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
30.0 dc End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
End Application: Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Radar set an/spg-51c Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Inclosure Type: Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Uninclosed Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Mounting Method: Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Panel Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Features Provided: Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Rfi shielding Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
Nonpile-up Contact Arrangement: 2 pole, double throw, one position momentary single switch unit						
2 pole, double throw, one position momentary single switch unit						
Contact Load Current Rating At Maximum Rated Voltage:						
1.000 amperes resistive dc and 0.500 amperes inductive dc						
Precious Material And Location:						
Contacts gold						
Terminal Type And Quantity:						
Terminal Type And Quantity.						
5 tab, solder lug and 6 turret						

N/a

NSN 5930-01-242-7080

Push Switch - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A053a0