# NSN 5930-01-243-3937

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-243-3937

## **Body Style:**

Panel mount

## Hazardous Locations/environmental Protection:

Shock resistant

# **Overall Length:**

1.200 inches

#### **Overall Height:**

3.111 inches

#### **Overall Width:**

0.960 inches

Body Length:

Between 1.075 inches and 1.105 inches

#### **Body Width:**

Between 0.835 inches and 0.865 inches

#### **Body Height:**

## 2.970 inches

Case Material:

Metal

#### Actuator Length:

1.040 inches

## Actuator Style:

Rectangular

#### Actuator Height:

0.140 inches

#### Actuator Width:

0.800 inches

## Actuator Color:

White single actuator and white single actuator

## Illuminated Actuator Color:

Green single actuator and white single actuator

#### **Actuator Inscription:**

Standby command standby complete single actuator

## Illuminated Actuator Color Sequence:

Upper half of actuator white lower half of actuator green

## Maximum Voltage Rating In Volts:

30.0 dc

## **End Application:**

Radar set an/spg-51c

Inclosure Type:

Fully enclosed

#### **Mounting Method:**

Panel

# NSN 5930-01-243-3937

Push Switch - Page 2 of 2



# Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 500.000 milliamperes inductive dc

#### **Special Features:**

Split lens

# Precious Material And Location:

Contacts gold

## **Terminal Type And Quantity:**

6 turret and 5 tab, solder lug

#### Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A053a0