NSN 5930-01-244-1654

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-244-1654

| View Online at https://aerobasegroup.com/nsn/5930-01-244-1654 |
|--|
| Overall Length: |
| 10.005 inches |
| Overall Height: |
| 3.187 inches |
| Overall Width: |
| 2.375 inches |
| Shaft Diameter: |
| 0.371 inches single actuator and 0.373 inches single actuator |
| Shaft Length: |
| 1.380 inches single actuator |
| Unthreaded Mounting Hole Diameter: |
| 0.150 inches single mounting facility |
| Individual Section Quantity: |
| 10 |
| Longest Horizontal Distance Between Mounting Centers: |
| 7.620 inches single mounting facility |
| Longest Vertical Distance Between Mounting Centers: |
| 1.750 inches single mounting facility |
| Switch Contact Basic Design: |
| Nonpile-up nonsymmetrical |
| Mounting Method: |
| Base single mounting facility and unthreaded hole single mounting facility |
| Contact Voltage Rating In Volts: |
| 500.0 ac at sea level |
| Mounting Facility Pattern: |
| Four position rectangular single mounting facility |
| Switch Actuator Indexing Position Quantity: |
| 5 single actuator |
| Shaft Type: |
| Round, threaded hole single actuator |
| Terminal Type: |
| Screw |
| Switch Actuator Positioning Increment: |
| 36.0 degrees single actuator |
| Switch Actuator Stop Device Type: |
| Fixed stop single actuator |
| Contact Load Current Rating: |
| 15.0 amperes resistive load ac at sea level |
| Style Designator: |
| In-line, cam actuated |
| Shelf Life: |

N/a

NSN 5930-01-244-1654Rotary Switch - Page 2 of 2



| ı | In | it I | Of | · M | دما | e i | ıre: |
|---|----|------|----|-----|-----|-----|------|
| ι | JΝ | II ' | ωı | IV | еа | SU | ıre: |

Demilitarization:

No

Fiig:

A052b0