

View Online at <https://aerobasegroup.com/nsn/5930-01-244-3345>

Inside Diameter:

0.250 inches single connection

Hazardous Locations/environmental Protection:

Explosion proof

Overall Length:

8.070 inches

Overall Height:

3.300 inches

Overall Width:

4.750 inches

Unthreaded Mounting Hole Diameter:

0.265 inches

Distance Between Mounting Facility Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket and unthreaded hole

Features Provided:

Hermetically sealed case

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

250.00 pounds per square inch

Thread Size:

0.250 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Wire lead

Contact Load Current Rating:

6.0 amperes resistive load second voltage and 5.0 amperes inductive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.00/+28.50 actuation point inches of mercury

Contact Adjustment Type:

Internal actuation point screw with scale

Contact Voltage Rating In Volts:

480.0 ac at sea level first voltage

Pressure Connector Type:

Plain, threaded internal single connection

Frequency In Hertz:

50.0 first voltage and 60.0 first voltage

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0