## NSN 5930-01-244-3433

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-244-3433

Over	all l	en	ath:	
	all I	Len	uui.	

Between 0.322 inches and 0.366 inches

**Overall Height:** 

Between 0.065 inches and 0.095 inches

**Body Diameter:** 

Between 0.248 inches and 0.278 inches

**Tempurature Sensing Element Type:** 

Internal sensor

**Mounting Method:** 

Clamp

**Features Provided:** 

Hermetically sealed case

**Contact Action Stimulus:** 

Increase

#### **Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:** 

Wire lead

#### **Contact Load Current Rating:**

500.0 milliamperes resistive load second voltage and 500.0 milliamperes inductive load second voltage and 200.0 milliamperes lamp load second voltage

#### **Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

#### **Contact Stimulus Rating:**

197.00 actuation point degrees fahrenheit and 213.00 actuation point degrees fahrenheit and 167.00 deactuation point degrees fahrenheit and 30.00 differential point degrees fahrenheit

### **Contact Voltage Rating In Volts:**

28.0 dc at sea level second voltage

Frequency In Hertz:

60.0 first voltage

Media For Which Designed:

Gas or liquid

**Style Designator:** 

Disc

#### **Test Data Document:**

81349-mil-s-24236 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-s-24236/13 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

-

Demilitarization:

# NSN 5930-01-244-3433

Thermostatic Switch - Page 2 of 2



Fiig:

A048b0