## NSN 5930-01-244-4618

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-244-4618

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

3.750 inches

**Overall Height:** 

1.531 inches

**Overall Width:** 

1.312 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.560 inches single actuator

**Nonturn Device Radius:** 

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Operating Tempurature Range:** 

-25.0/+85.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

6 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Rotor Through Connection Quantity:** 

2 each section

**Switch Actuator Indexing Position Quantity:** 

6 single actuator

**Shaft Type:** 

Round, breakoff single actuator

**Terminal Type:** 

Tab, solder lug

## NSN 5930-01-244-4618

Rotary Switch - Page 2 of 2



## **Contact Switching Action:**

Breaks before makes each section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed-adjustable stops single actuator

**Contact Load Current Rating:** 

500.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

## **Demilitarization:**

Yes - demil/mli

Fiig:

A052b0