# NSN 5930-01-244-6476

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-244-6476



# **Body Style:**

Panel mounted

## Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

## **Overall Length:**

3.706 inches

#### **Overall Height:**

0.890 inches

#### **Overall Width:**

0.890 inches

### **Body Width:**

0.750 inches

#### **Body Height:**

0.679 inches

#### Case Material:

Metal

#### . . . . .

Actuator Length:

0.620 inches

# Actuator Style:

Rectangular

## Actuator Height:

0.100 inches

### Actuator Width:

0.620 inches

## Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

White single actuator

### Actuator Inscription:

On off single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac

# **End Application:**

Missile guidance and tracking set an/spg-55b

# Mounting Surface To Terminal End Distance:

3.560 inches

# Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

# **Features Provided:**

Actuator seal and holding solenoid and full display lens

# NSN 5930-01-244-6476

Push Switch - Page 2 of 2



# Nonpile-up Contact Arrangement:

2 pole, double throw, both positions maintained single switch unit

## Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive ac and 3.500 amperes inductive ac

**Precious Material And Location:** 

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0