NSN 5930-01-244-9490

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-244-9490 **Body Style:** Hole mounted **Overall Length:** 3.040 inches **Overall Height:** 2.953 inches **Actuator Style:** Roller plunger **Actuator Free Position Height:** 1.953 inches **Actuator Roller Diameter:** 0.500 inches **Actuator Roller Width:** 0.160 inches **Housing Height:** 1.750 inches **Housing Width:** 1.000 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Length: 1.000 inches **Maximum Voltage Rating In Volts:** 480.0 ac and 250.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole **Nonpile-up Contact Arrangement:** 1 pole, double throw, one position momentary single switch unit **Switch Release Force:** 4.0 ounces **Switch Actuating Force:** Between 9.0 ounces and 13.0 ounces **Actuator Movement:** 0.020 pretravel inches and 0.140 overtravel inches and 0.002 differential inches **Contact Load Current Rating At Maximum Rated Voltage:** 250.000 milliamperes resistive dc and 20.000 amperes resistive ac **Terminal Type And Quantity:** 3 tab w/screw Shelf Life: N/a **Unit Of Measure:**

--

NSN 5930-01-244-9490

Sensitive Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0