## NSN 5930-01-244-9491

Slide Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-244-9491

Body Style:
Hole mounted
Overall Length:
0.680 inches
Overall Height:
0.500 inches
Overall Width:
Between 0.370 inches and 0.405 inches
Body Length:
0.680 inches
Body Width:
Between 0.370 inches and 0.405 inches
Body Height:
Between 0.230 inches and 0.300 inches
Case Material:
Plastic
Switch Actuator Quantity:
6
Actuator Length:
Between 0.045 inches and 0.065 inches
Actuator Height:
0.040 inches
Actuator Width:
Between 0.055 inches and 0.085 inches
Actuator Position-action Relationship:
Left position maintained and right position maintained
Maximum Voltage Rating In Volts:
24.0 dc
End Application:
5820-01-145-4899 control, orderwire
Nonpile-up Contact Arrangement:
6 pole, single throw, both positions maintained single switch unit
Contact Load Current Rating At Maximum Rated Voltage:
25.000 milliamperes resistive dc
Special Features:
Terminal mounted
Test Data Document:
81349-mil-s-83504 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
12 printed circuit

81349-mil-s-83504/4 government specification

**Specification Data:** 

## NSN 5930-01-244-9491

Slide Switch - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0