# NSN 5930-01-244-9493

Push Switch - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5930-01-244-9493

#### Body Style:

Panel mount

#### Hazardous Locations/environmental Protection:

Explosion proof

## **Overall Length:**

0.740 inches

#### **Overall Height:**

3.220 inches

#### **Overall Width:**

0.740 inches

#### **Body Length:**

0.679 inches

#### Body Width:

0.679 inches

#### **Body Height:**

2.896 inches

# Actuator Length:

0.740 inches

#### 0.7 40 1101103

Actuator Style:

Rectangular

#### Actuator Height:

0.270 inches

#### Actuator Width:

0.740 inches

#### Actuator Color:

White single actuator

#### **Illuminated Actuator Color:**

Natural single actuator

#### **Actuator Inscription:**

10 single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### **End Application:**

Signal processing set an/syq-8

### Inclosure Type:

Fully enclosed

# **Mounting Method:**

Panel

#### **Features Provided:**

Actuator seal

#### **Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-244-9493

Push Switch - Page 2 of 2



# Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

# Precious Material And Location:

Contacts silver

# Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0