NSN 5930-01-244-9496

Push Switch - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5930-01-244-9496



Body Style:

Panel mounted

Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

Overall Length:

3.220 inches

Overall Height:

0.750 inches

Overall Width:

0.750 inches

- **Body Width:**
- 0.750 inches

Body Height:

0.750 inches

Actuator Length:

0.740 inches

Actuator Style:

Rectangular

Actuator Height:

0.270 inches

Actuator Width:

0.740 inches

Actuator Color:

White single actuator

Illuminated Actuator Color:

Natural single actuator

Actuator Inscription:

5 single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

End Application:

Signal processing set an/syq-8

Mounting Surface To Terminal End Distance:

2.756 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Panel

Features Provided:

Actuator seal and full display lens

Nonpile-up Contact Arrangement:

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-244-9496

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes

inductive ac and 1.000 amperes lamp ac

Precious Material And Location:

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0