

View Online at <https://aerobasegroup.com/nsn/5930-01-245-1468>

Thread Class:

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

Overall Length:

5.955 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.437 inches single actuator

Overall Diameter:

1.284 inches

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

12

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section front

Throw Quantity:

8 each section rear

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

0.03 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Rotor Through Connection Quantity:

1 each section

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Criticality Code Justification:

Zzzy

Terminal Type:

Connector, plug

Contact Switching Action:

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Contact Load Current Rating:

10.0 milliamperes resistive load dc at sea level

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3551

Precious Material And Location:

Contact surfaces gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unef single mounting facility

Reference Number Differentiating Characteristics:

Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0