## NSN 5930-01-245-1469

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-245-1469

**Thread Class:** 

2a single mounting facility

Thread Length:

0.437 inches single mounting facility

**Overall Length:** 

2.245 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.437 inches single actuator

**Overall Diameter:** 

1.284 inches

**Nonturn Device Radius:** 

0.531 inches at 3: 00 o'clock

**Individual Section Quantity:** 

2

**Nonturn Device Type:** 

Tab at 3: 00 o'clock

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 each section front

**Throw Quantity:** 

5 each section rear

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

0.03 dc at sea level

**Shaft Flat/slot Angular Location:** 

180.0 degrees from contact position 1 single actuator

**Rotor Through Connection Quantity:** 

2 each section

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round, flatted single actuator

## **NSN 5930-01-245-1469**Rotary Switch - Page 2 of 2



Criticality Code Justification:
Zzzy
Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes each section rear
Switch Actuator Positioning Increment:
30.0 degrees single actuator
Contact Load Current Rating:
10.0 milliamperes resistive load dc at sea level
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3545
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Style Designator:
Tap, circular, bushing mount
Thread Series Designator:
Unef single mounting facility
Reference Number Differentiating Characteristics:
Breference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp.
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Filig:
A052b0