NSN 5930-01-245-1474

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-01-245-1474

Body Style:
Panel mount
Hazardous Locations/environmental Protection:
Explosion proof
Overall Length:
0.740 inches
Overall Height:
3.220 inches
Overall Width:
0.740 inches
Body Length:
0.679 inches
Body Width:
0.679 inches
Body Height:
2.896 inches
Actuator Length:
0.740 inches
Actuator Style:
Rectangular
Actuator Height:
0.270 inches
Actuator Width:
0.740 inches
Actuator Color:
White single actuator
Illuminated Actuator Color:
Natural single actuator
Actuator Inscription:
3 single actuator
Maximum Voltage Rating In Volts:
115.0 ac and 28.0 dc
End Application:
Signal processing set an/syq-8
Inclosure Type:
Fully enclosed
Mounting Method:
Panel
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

NSN 5930-01-245-1474

Push Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.500 amperes inductive ac and 1.000 amperes lamp ac

Precious	Material	And	Location:
----------	----------	-----	-----------

Contacts silver

Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0