NSN 5930-01-245-1476

Push Switch - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5930-01-245-1476 |
|---|
| Body Style: |
| Panel mount |
| Hazardous Locations/environmental Protection: |
| Explosion proof |
| Overall Length: |
| 0.750 inches |
| Overall Height: |
| 3.346 inches |
| Overall Width: |
| 0.750 inches |
| Body Length: |
| 0.679 inches |
| Body Height: |
| 3.076 inches |
| Case Material: |
| Metal |
| Actuator Length: |
| 0.740 inches |
| Actuator Style: |
| Rectangular |
| Actuator Height: |
| 0.270 inches |
| Actuator Width: |
| 0.740 inches |
| Actuator Color: |
| White single actuator |
| Illuminated Actuator Color: |
| Natural single actuator |
| Actuator Inscription: |
| 9 single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Panel |
| Features Provided: |
| Actuator seal |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

NSN 5930-01-245-1476

Push Switch - Page 2 of 2



| Precious Material And Location: |
|---------------------------------------|
| Contacts silver |
| Terminal Type And Quantity: |
| 1 socket, integrated wire termination |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A053a0